



PRODUCT DATA SHEET

TSW-2 Multi-Master™

Multi-Purpose Stain & Graffiti Remover for Most Surfaces

TSW-2 Multi-Master™ is an aggressive, biodegradable blend perfect for everyday removal, and safe for volunteer organizations. TSW-2 Multi-Master™ will quickly remove spray paint, permanent marker, and other graffiti from a wide variety of surfaces. Always test, rinse, and dry a small inconspicuous area first, as the solvents will damage some surfaces. TSW-2 Multi-Master is easy to use, Spray the effected area and wipe or scrub and rinse. Do not attempt an area so large that Multi-Master will evaporate before you complete the removal process. (Avoid use in direct sunlight when surfaces are warm to the touch.) Do not attempt removal from wet surfaces, as moisture will limit effectiveness of product. If TSW-2 Multi-Master is too aggressive we recommend our TSW-1 Plasti-Master™. TSW-2 Multi-Master is not recommended for vehicles. Never dilute with other liquids. Never add water or solvent action will be destroyed.

TO REMOVE PERMANENT MARKER: From **Paint:** Spray and immediately soak up suspended dyes & pigments with clean rag before they stain surrounding area. Repeat until graffiti is gone then rinse with water. Light scrubbing may be necessary. Avoid cleaning through the paint film. **From Natural Surfaces:** Repeat above steps, blotting to remove suspended graffiti. For stubborn stains use Multi-Master as a poultice re-applying on consecutive days until stain is gone. A pressure washer may be necessary. **From Hard Surfaces:** (e.g. Formica, steel doors, traffic boxes, etc.) Spray and immediately wipe with clean dry rag or paper towel.

TO REMOVE SPRAY PAINT: From **Natural Surfaces:** Spray until saturated. Allow sufficient time for solvent action to begin. (A few seconds to a few minutes). Agitate with stiff bristle brush until all graffiti is in suspension. It may be necessary to re-apply remover. Hose pressure is often adequate but on porous surfaces a pressure washer may be necessary. **From Hard Surfaces:** (e.g. Formica, steel doors, traffic boxes, etc.) Spray on, agitate with stiff bristle brush, and when solvent action is complete flush residue with water from bucket, pump sprayer, hose or pressure washer as necessary. If removal is incomplete, dry and repeat above steps. **From Paint:** For small areas follow instructions for hard finished surfaces.

IMPORTANT NOTE - Some formulations of spray paint will not respond to TSW-2 Multi-Master. For these paints a preliminary application of Multi-Master followed by our Mason-Master remover will drastically improve the results! When Multi-Master is not sufficient spray (or roll) effected area with Multi-Master first, followed by a thorough saturation with Mason-Master. Allow sufficient time for solvents to work. Repeat applications may be necessary. Practice will determine proper technique & solvent combination to achieve complete removal. Follow instructions or call for more information.

HEALTH & SAFETY INFORMATION - As with any chemical, appropriate precautions for chemical contact must be taken. Wear chemical resistant butyl or neoprene rubber gloves. Wear eye protection. Avoid contact with skin. Can cause irritation to skin & eyes. Use with adequate ventilation. If swallowed induce vomiting. For skin contact wash with soap and water – rinse for fifteen minutes. For eye contact flush with large amounts of water. If irritation persists contact a physician. For additional information consult Material Safety Data Sheet or call our Customer Help Line at 800-447-2334 (800 4 GRAFFITI). TSW-2 Multi-Master is packaged in 22oz spray, one gallon, and fifty-five gallon quantities.

Sales & Technical Support: 800-447-2334 / 800-4-GRAFFITI-----Fax 925-443-5209

www.graffitimaster.com