



# MATERIAL SAFETY DATA SHEET

This Stuff Works, Inc  
2021 Las Positas Ct. #147  
Livermore, CA 94551

Daytime Phone: 800-447-2334

Emergency: Chemtel: 800-255-3924

Date Compiled: 01 June 2005

## SECTION 1: PRODUCT IDENTIFICATION

**Product name: TSW-3 Mason-Master**

Synonym/Chemical name/Common name: Graffiti Remover

DOT hazard class: Corrosive

DOT proper shipping name: Corrosive liquids, N.O.S. (Potassium Hydroxide), 8, UN 1760, PG II

## SECTION 2: INGREDIENT INFORMATION

Hazardous Ingredients	Wgt %	Toxicity Data
Potassium Hydroxide* CAS# 1310-58-3	TRADE SECRET	TLV=2 mg/m3 in air
Butyl Cellosolve CAS# 111-76-2	PER CFR 1910.1200	TLV=121 mg/m3 in air

This product contains no chemical at a level, which poses a significant risk as defined by California Proposition 65.

\*This chemical is subject to reporting requirements of Title III SARA, section 313 EPCRA (40 CFR 372).

## SECTION 3: PHYSICAL CHARACTERISTICS

Specific Gravity (H2O=1): 1.026  
Vapor pressure: 24 mm Hg  
Vapor density (Air=1): No vapors are produced  
Percentage volatile by weight: 82.1  
Solubility in water: Complete  
pH (Undiluted): 13.5 to 14.0  
Evaporation rate (H2O=1): 1.0  
Freezing point: 32o F  
Boiling point: 212o F  
Appearance and odor: Clear liquid with mild solvent odor

Product name: **TSW-3 Mason-Master** (Page 2)

**SECTION 4: FIRE AND EXPLOSION HAZARDS**

Flash point: Nonflammable  
Flash point test method: N/A  
Flammability limits: N/A  
Extinguishing media: Treat primary fire  
Special fire fighting procedures: None  
Unusual fire or explosive hazards: None

**SECTION 5: REACTIVITY DATA/CONDITIONS TO AVOID**

Stability: Stable  
Incompatibilities (Conditions to avoid): Do not mix with acids  
Hazardous decomposition products: None  
Hazardous polymerization will not occur.  
Conditions to avoid: None are known

**SECTION 6: HEALTH HAZARDS/FIRST AID**

Primary routes of entry: Skin & eyes  
Signs and symptoms: Product is extremely irritating to unprotected skin and is destructive to eyes.  
First aid procedures: For skin contact flush with large amounts of water. For eye contact, flush with water for at least 15 minutes and contact a physician. If swallowed do not induce vomiting. Contact a physician or poison control center.  
There are no known chronic health effects caused by the use of this product.

**SECTION 7: PERSONAL PROTECTION RECOMMENDATIONS**

Respiratory protection: None required  
Ventilation: Use with adequate ventilation  
Protective gloves: Neoprene gloves are mandatory for hands.  
Eye protection: Chemical goggles and/or face shield must be worn during use to prevent eye contact. Avoid sprayed mists.

**SECTION 8: STORAGE/SPILL/SPECIAL HANDLING INFORMATION**

Steps to be taken in case of spill: Spill area will be slippery until spilled material is removed.  
Remove with rags, mops, or by flushing with water - use best management practices.  
Waste disposal: Follow all local, state, and federal waste disposal regulations.  
Special storage or handling precautions: Do not expose to freezing temperatures.

N/D = Not determined      N/A = Not applicable

This Material Safety Data Sheet is written and provided in good faith for the sole purpose of providing information for the safe use and handling of this product. It is compiled from technical data believed to be current and correct. It should not be taken as a warranty or representation for which T.S.W., Inc assumes any legal responsibility. The buyer assumes all responsibilities of using and handling the product in accordance with local, state, and federal regulations.

**Manufactured by This Stuff Works, Inc. All rights reserved.**  
**Phone: 800-447-2334 / Fax: 925-443-5209 / [www.graffitimaster.com](http://www.graffitimaster.com)**