



PRODUCT DATA SHEET

TSW-3 Mason-Master™

GRAFFITI REMOVER (For: Concrete, Stone, Brick, and other Natural Surfaces)

TSW-3 Mason-Master™ is specifically formulated to remove spray paint and other common graffiti from concrete, stone, and most other natural surfaces. Mason-Master is a mixture of solvent and alkali. Always test, rinse, and dry a small inconspicuous area first. TSW-3 Mason-Master will damage some alkali sensitive surfaces. Some types of spray paint remove best when TSW-3 Mason-Master™ is used in conjunction with our TSW-2 Multi-Master™ remover (see instructions below). When all graffiti is in suspension, rinse residue with high-pressure water.

GRAFFITI REMOVAL - Spray TSW-3 Mason-Master on the affected area, or for large areas, apply TSW-3 Mason-Master with a paint roller. Protect against eye and skin contact. Continue application until area is saturated. Do not attempt an area so large that TSW-3 Mason-Master will evaporate before you can pressure wash. Note - On large hits work from the bottom up. Clean a small area and continue until graffiti is removed (Note: Keep adjacent areas dry until remover is applied). Avoid use in direct sunlight or when surfaces are warm to the touch to slow evaporation. Apply as directed. Agitate with a stiff bristle brush. When solvent action appears complete and all graffiti appears loosened use high-pressure water to remove graffiti, a pressure washer is generally recommended. Rinse at the rate of 32 parts water to 1 part TSW-3 Mason-Master to bring ph below 12.5. Contain run-off and use best management practices. If removal is incomplete allow surface to dry then re-apply and repeat as necessary.

IMPORTANT NOTE - Some formulations of spray paint will not respond to TSW-3 Mason-Master alone and you will need a preliminary application of our TSW-2 Multi-Master remover to compliment the effects of TSW-3 Mason-Master. When TSW-3 Mason-Master is not sufficient spray (or roll) affected area with TSW-2 Multi-Master first, followed by a thorough saturation with TSW-3 Mason-Master. Allow sufficient time for solvents to work. Repeat applications may be necessary. A little practice will determine proper technique & combination. Follow label instructions.

SAFETY INFORMATION – TSW-3 Mason-Master™ is a corrosive blend of alkali and solvents. Use with adequate ventilation. TSW-3 Mason-Master is destructive to eyes and skin and appropriate precautions must be taken. Wear Neoprene gloves. Wear chemical goggles. Protect skin and eyes from exposure. Protect passerby, vehicles, plants, and other surfaces from contact. **FIRST AID:** For skin contact, flush with large amounts of water. For eye contact flush with water for at least fifteen minutes and contact physician. If swallowed do not induce vomiting. Contact a physician, poison control center, or CHEM-TEL @ 800-255-3924. There are no known chronic health problems associated with the use of this product. For additional safety information consult Material Safety Data Sheet or call our Consumer Hotline at 800-447-2334 (800 4 GRAFFITI). To avoid incompatibility do not thin or add other liquids to TSW-3 Mason-Master. TSW-3 Mason-Master is packaged in 22oz Spray, one gallon, and fifty-five gallon quantities. Caution: TSW-3 Mason-Master contains corrosive ingredients.

Sales & Technical Support: 800-447-2334-----800-4-GRAFFITI-----Fax: 925-443-5209

www.graffitimaster.com