



PRODUCT DATA SHEET

TSW3 Mason-Master™

HEAVY DUTY GRAFFITI REMOVER

(For: Concrete, Stone, Brick, and other Natural Non-Painted Surfaces)

TSW3 Mason-Master™ is specifically formulated to remove spray paint and other common graffiti from concrete, stone, and most other natural surfaces. Mason-Master is a mixture of solvent and alkali. **Always test, rinse, and dry a small inconspicuous area first.** TSW3 Mason-Master will damage some alkali sensitive surfaces. Some types of spray paint remove best when TSW3 Mason-Master™ is used in conjunction with our TSW2 Multi-Master™ remover (see instructions below). When all graffiti is in suspension, rinse residue with high-pressure water (1800psi+).

GRAFFITI REMOVAL - Spray TSW3 Mason-Master on the affected area, or for large areas, apply TSW3 Mason-Master with a paint roller. Protect against eye and skin contact. Continue application until area is saturated. Do not attempt an area so large that TSW3 Mason-Master will evaporate before you can pressure wash. Note - On large hits work from the bottom up. Clean a small area and continue until graffiti is removed (Note: Keep adjacent areas dry until remover is applied). Avoid use in direct sunlight or when surfaces are warm to the touch to slow evaporation. Apply as directed. Agitate with a stiff bristle brush. When solvent action appears complete and all graffiti appears loosened, use high-pressure water to remove graffiti. A pressure washer is generally recommended. Contain run-off and use best management practices. If removal is incomplete allow surface to dry then re-apply and repeat as necessary.

IMPORTANT NOTE - Some formulations of spray paint will not respond to TSW3 Mason-Master alone and you will need a preliminary application of our TSW2 Multi-Master remover to compliment the effects of TSW3 Mason-Master. When TSW3 Mason-Master is not sufficient spray (or roll) affected area with TSW2 Multi-Master first, followed by a thorough saturation with TSW3 Mason-Master. Allow sufficient time for solvents to work. Repeat applications may be necessary. A little practice will determine proper technique & combination. Follow label instructions.

SAFETY INFORMATION – TSW3 Mason-Master™ is a corrosive blend of alkali and solvents. Use with adequate ventilation. TSW3 Mason-Master is destructive to eyes and skin and appropriate precautions must be taken. Wear chemical resistant gloves. Wear chemical resistant glasses/goggles. Protect skin and eyes from exposure. Protect passerby, vehicles, plants, and other surfaces from contact. **FIRST AID:** For skin contact, flush with large amounts of water. For eye contact flush with water for at least fifteen minutes and contact physician. If swallowed do not induce vomiting. Contact a physician, poison control center, or CHEM-TEL @ 800-255-3924. There are no known chronic health problems associated with the use of this product. For additional safety information consult Material Safety Data Sheet or call our Consumer Hotline at 800-447-2334 (800 4 GRAFFITI). To avoid incompatibility do not thin or add other liquids to TSW3 Mason-Master. TSW3 Mason-Master is packaged in 22oz Spray, one gallon, thirty and fifty-five gallon quantities. Caution: TSW3 Mason-Master contains corrosive ingredients.

Sales & Technical Support: 800-447-2334-----800-4GRAFFITI-----Fax: 925-443-5209

www.TSWwarehouse.com