



PRODUCT DATA SHEET

TSW1 / Plasti-Master™

Graffiti Remover & Industrial Strength Cleaner for Delicate Surfaces

(For: Vehicles, Plastics, Glass, Aluminum & Many Other Surfaces)

TSW-1/Plasti-Master™ is a unique blend of solvents and detergents specifically formulated to remove graffiti & defacement from Plastics, Glass, Aluminum, Vehicles, and many other hard finished surfaces. It is also effective when used to remove painters' overspray (Latex & Oil). TSW-1/Plasti-Master™ is our least aggressive formula. **Always test, rinse, and dry a small inconspicuous area for compatibility first** as the solvents will damage some surfaces. TSW-1/Plasti-Master™ is easy to use. Simply spray the effected area then wipe or brush and rinse. Use as supplied. Never dilute with any other liquids. Do not attempt an area so large that TSW-1/Plasti-Master™ will evaporate or the surface will be damaged before you complete the process. (Avoid use in direct sunlight when surfaces are warm to the touch.) In many instances our more aggressive products; TSW2/Multi-Master™ or TSW3/Mason-Master™ will outperform TSW1/Plasti-Master™. Follow label directions or call for specific instructions.

TO REMOVE PERMANENT MARKER: *From Vehicles* - Spray remover and immediately wipe with clean rag repeating as necessary. Rinse immediately with water. **Note:** Test small inconspicuous area first - if remover damages vehicle finish, discontinue use. If removal is incomplete call our Helpline for additional instructions. ***From Paint*** - Spray remover and immediately soak up suspended dyes & pigments with clean rag before they stain-surrounding area. Repeat until graffiti is gone then rinse with water. Some light scrubbing may be necessary but be careful to avoid cleaning through the paint film. ***From Natural Surfaces*** - Repeat above steps, blotting to remove suspended graffiti. ***From Hard or Protected Surfaces*** - (e.g. Formica, steel doors, traffic boxes, etc.) Spray remover and wipe with clean dry rag or paper towel. Repeat as necessary and rinse with water when finished. **NOTE:** For more stubborn graffiti use our TSW2/Multi-Master™ and/or TSW3/Mason-Master™ removers and follow directions on their labels.

TO REMOVE SPRAY PAINT: *From Vehicles* - Spray remover on a small area and allow brief dwell time, wipe with clean rag (a soft bristle nylon brush may be necessary) repeat as necessary and rinse immediately with water continuing until all paint is removed. **Note:** Test small inconspicuous area first - if removal process damages vehicle finish, discontinue use. If removal is incomplete call our Helpline for additional instructions. ***From Paint*** - For small areas follow above instructions for hard finished surfaces. **NOTE:** For more stubborn stains & graffiti, use TSW2/Multi-Master™ and/or TSW3/Mason-Master™ removers and follow directions on their labels.

SAFETY INFORMATION - Plasti-Master is a Flammable Liquid. Use with adequate ventilation. Do not expose to fire or flame. As with any chemical, appropriate precautions must be taken. Chemical resistant gloves are recommended for long or repeated contact. Eye protection is recommended. Prolonged contact will dry skin. **FIRST AID:** For eye contact flush with large amounts of water for at least fifteen minutes. If irritation persists contact a physician. For skin contact flush with large amounts of water. If swallowed do not induce vomiting. Give two glasses of water and orange or lemon juice. Contact a physician. There are no known chronic health problems associated with the use of this product. TSW1/Plasti-Master is packaged in 22oz., one gallon, thirty and fifty-five gallon quantities. For additional safety information consult Material Safety Data Sheet or call our Help Line at 800-447-2334 (800-4GRAFFITI). Emergency call Chemtel 800-255-3924.

NOTE: If you have difficulty removing graffiti please call our Help Line at 1-800-4-GRAFFITI or (800-447-2334).

Sales: 800-447-2334 ----- Help: 800-4-GRAFFITI-----Fax – 925-443-5209
www.TSWwarehouse.com