

PRODUCT DATA SHEET



TSW2 Multi-Master™ Graffiti and Stain Remover for Most Surfaces

DEVELOPED TO REMOVE: Graffiti and Stains consisting of Oil and Latex Paints, Permanent Marker, Pen, Inks, Lipstick, Correction Fluid, Tar, Oil and More!

FROM: Most surfaces including but not limited to paint, carpet, clothing and much more.

DIRECTIONS: *Always test, rinse, and dry a small inconspicuous area for compatibility first!*

1. **Spray directly on surface**
2. **Wipe with clean cloth or sponge**
3. **Neutralize with TSW7™ or water**

Note: For large areas, clean in sections. Not doing so could result in product evaporation prior to completing removal process. Avoid use in direct sunlight or when surfaces are warm to the touch. Product effectiveness is limited at temperatures below 45° and above 95° Fahrenheit. Use as supplied. Never dilute with any other liquids.

When removing marker apply remover then immediately blot with clean cloth or sponge. Suspended dyes and pigments must be soaked up, not doing so could result in staining surrounding area. Repeat until graffiti is gone, neutralize with TSW7™ or water. Light scrubbing may be necessary.

When removing spray paint allow sufficient time for TSW2™ to react (this may take a few seconds to a few minutes), agitate with cloth or sponge, then neutralize with TSW7™ or water.

Thicker layers of defacement may require use of a scrub brush. Repeat applications may be necessary. Removal from unpainted porous surfaces typically requires use of a pressure washer and TSW3 Mason-Master™ for improved results. If TSW2™ is too aggressive for your surface, try TSW1 or TSW9 Plasti-Master™.

HEALTH AND SAFETY INFORMATION – KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation. Wear chemical resistant gloves and eye protection. Avoid skin contact as TSW2™ can cause irritation to skin and eyes. **FIRST AID:** For skin contact, wash with soap and water. In case of eye contact flush with large amounts of water. If swallowed, DO NOT INDUCE VOMITING. If irritation persists, seek medical attention. Use of this product causes no known chronic health effects.

Packaging: TSW2 Multi-Master™ is packaged in 22oz. spray, one gallon, five gallon, thirty and fifty-five gallon quantities.

For complete safety information refer to MSDS or call customer support at 800.447.2334.

CHEM-TEL 24-Hour Emergency Contact # 800.255.3924

Visit our website www.TSWwarehouse.com

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)