

# PRODUCT DATA SHEET



## TSW3G Mason-Master™ (GEL)

Graffiti Remover for Unpainted Porous Surfaces

**DEVELOPED TO REMOVE:** Spray paint and other common graffiti vandalism!

**FROM:** Concrete, Brick, Stone and most other unpainted porous surfaces.

**\*\*READ HEALTH AND SAFETY INFORMATION PRIOR TO USE\*\***

**DIRECTIONS:** Always test, rinse, and dry a small inconspicuous area for compatibility first! Wear protective gear as noted in HEALTH AND SAFETY.

1. Spray directly on surface
2. Agitate affected area with a stiff bristle brush\*
3. When solvent action appears complete and graffiti is loosened, use a pressure washer to remove defacement.

\*Allow sufficient time for TSW3G to react (this may take a few seconds for permanent marker to a few minutes for spray paint).

**Note:** For large areas, clean in sections. Not doing so could result in product evaporation prior to removal or pressure washing. Begin removal by working from the bottom up as opposed to the top down. Avoid use in direct sunlight or when surfaces are warm to the touch. Product effectiveness is limited at temperatures below 45° and above 95° Fahrenheit. Use as supplied. Never dilute with any other liquids. TSW7™ and water neutralizes TSW3G™ – Use on dry surfaces only.

Repeat applications may be necessary. A preliminary application of TSW2 or TSW2G Multi-Master™ may be required on some surfaces for improved results. When TSW3G Mason-Master™ is not sufficient, spray affected area with TSW2 or TSW2G Multi-Master™ first, followed by a thorough saturation of TSW3G Mason-Master™.

**HEALTH AND SAFETY INFORMATION – Caution: Corrosive Liquid** – Extremely irritating to skin and destructive to eyes. KEEP OUT OF REACH OF CHILDREN. Contains a blend of alkali and solvents – Containing runoff is recommended and mandatory in certain jurisdictions. Avoid contact with skin and eyes as TSW3G™ is extremely irritating to skin and destructive to eyes. Use with adequate ventilation. Wear chemical resistant gloves and eye protection. Do not take internally. **FIRST AID:** In case of skin contact, flush with large amounts of water. In case of eye contact, flush with large amounts of water for at least 15 minutes and seek medical attention. If swallowed, DO NOT INDUCE VOMITING. Contact poison control center. There are no known chronic health effects caused by the use of this product.

**Packaging:** TSW3G (GEL) Mason-Master™ is packaged in 22oz. spray bottles, one gallon, five gallon, thirty and fifty-five gallon quantities.

For complete safety information refer to MSDS or call customer support at 800.447.2334.

**CHEM-TEL 24-Hour Emergency Contact # 800.255.3924**

Visit our website [www.TSWwarehouse.com](http://www.TSWwarehouse.com) Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)