

# PRODUCT DATA SHEET



## TSW5 Spray Clean™

Airless Paint Sprayer Cleaner

**DEVELOPED AT THE REQUEST OF PAINT SPRAY EQUIPMENT PROFESSIONALS TO:** Internally clean paint spray equipment and parts. (Breaks apart acrylics, latex and Acryli-Master)

**INSTRUCTIONS FOR INTERNAL CLEANING:** For cleanup after each job, add 4oz. of TSW5 to 3 gallons of fresh water. As a final rinse, run the solution using the same procedure as when painting through the entire apparatus. The final few ounces of water should be clear. If paint residue is still in the water, repeat the process. Do not store in apparatus.

**INSTRUCTIONS FOR CLEANING SPRAY EQUIPMENT PARTS:** To clean parts that are covered with hardened paint, add 8oz. of TSW5 to ½ gallon of water and soak the parts until the paint has softened and loosened from the surfaces (preferably overnight). Use a pick to remove from areas that are thickly coated.

**HEALTH AND SAFETY INFORMATION – KEEP OUT OF REACH OF CHILDREN.** Use with adequate ventilation. Wear rubber gloves and guard against splashing into eyes. Product is irritating to skin and extremely irritating into eyes. **FIRST AID:** For skin contact, flush with large amounts of water. For eye contact, flush with water for fifteen minutes. If irritation persists, seek medical attention. There are no known chronic health problems associated with the use of this product.

**Packaging:** TSW5 Spray-Clean™ is packaged in 4oz., 22oz. and one gallon quantities.

For complete safety information refer to MSDS or call customer support at 800.447.2334.

**CHEM-TEL 24-Hour Emergency Contact # 800.255.3924**

Visit our website [www.TSWwarehouse.com](http://www.TSWwarehouse.com)

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)