

# PRODUCT DATA SHEET



## TSW9 Plasti-Master™

Zero VOC Graffiti Remover for Delicate Surfaces

**DEVELOPED TO REMOVE:** Graffiti, Stains, Paint Overspray (latex and oil) and more!

**FROM:** Vehicles, Glass, Aluminum, and many other hard finished surfaces.

**DIRECTIONS:** *Always test, rinse, and dry a small inconspicuous area for compatibility first!*

1. **Spray directly on surface**
2. **Wipe with clean cloth or sponge**
3. **Neutralize with TSW7™ or water**

**Note:** For large areas, clean in sections. Not doing so could result in product evaporation prior to completing removal process. Avoid use in direct sunlight or when surfaces are warm to the touch. Product effectiveness is limited at temperatures below 45° and above 95° Fahrenheit. Use as supplied. Never dilute with any other liquids.

**When removing marker** apply remover then immediately blot with clean cloth or sponge. Suspended dyes and pigments must be soaked up, not doing so could result in staining surrounding area. Repeat until graffiti is gone, neutralize with TSW7™ or water.

**When removing spray paint** allow sufficient time for TSW9™ to react (this may take a few seconds to a few minutes) then neutralize with TSW7™ or water.

Thicker layers of defacement may require use of a scrub brush. For more stubborn stains & graffiti, use TSW2 Multi-Master™ and/or TSW3 Mason-Master™ removers and follow directions on their labels.

**HEALTH AND SAFETY INFORMATION** – KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation. Wear chemical resistant gloves and eye protection. Avoid contact with skin as TSW9™ can cause irritation to eyes and is sensitive to skin. **FIRST AID:** In case of eye contact, flush with large amounts of water. If swallowed, DO NOT INDUCE VOMITING. If irritation persists, seek medical attention. There are no known chronic health problems associated with the use of this product.

**Packaging:** TSW9 Plasti-Master™ is packaged in 22oz. spray, one gallon, five gallon, thirty and fifty-five gallon quantities.

For complete safety information refer to MSDS or call customer support at 800.447.2334.

**CHEM-TEL 24-Hour Emergency Contact # 800.255.3924**

Visit our website [www.TSWwarehouse.com](http://www.TSWwarehouse.com)

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)